



DRAWING LEGEND

SYMBOL	QTY.	DESCRIPTION
	1	125A, 125/240V ELECTRICAL PANEL
	2	8" FLOOR DRAIN
	1	MAIN WATER SUPPLY INLET
	1	120 GAL., 240V ELECTRIC WATER HEATER W/ PAN

FLOOR PLAN

NOTE:

BLOCKING MUST BE INSTALLED FROM THE FOUNDATION TO THE STEEL FRAME DIRECTLY UNDER THE WATER HEATER.

DOOR & WINDOW SCHEDULE

SYMBOL	QTY	DESCRIPTION	ROUGH OPENING
	2	3600 VINYL DOOR W/ 80" WINDOW, STAY CHAIN, KEYED KNOB LOCKSET & DEADBOLT	36x80 CLR TO 36x80 PER DETAIL
	2	3200 HOLLOW CORE W/ WOOD JAMB & PASSAGE KNOB LATCHSET	34 X 88 3/4
	1	3200 HOLLOW CORE W/ WOOD JAMB & KEYED KNOB LOCKSET	34 X 88 3/4
	5	3014 HORIZONTAL SLIDER W/ ALUM. FRAME, SINGLE PANE OBSCURE GLASS & SCREEN @ 66" A.F.F.	30 1/4 X 34 1/4



EXTERIOR DOOR FRAMING

1. SCREW A 1/4" TO THE BOTTOM OF THE DOOR HEADER FOR EASY REMOVAL.
2. SCREW A 2"x4" OVER A 2"x6" STEP OF DOOR TO THE JACK STUD FOR EASY REMOVAL.