

Framing for Exterior Door "A"

A 120/240v 12PV BRKT PANEL 60A 2-pole breaker 1 1/2" EMT conduit (2) #6 THW feeders #8 GND

Electrical Riser Diagram



DRAWING LEGEND

SYMBOL	QTY.	DESCRIPTION
▸	2	Over the floor hurricane straps/Tie down locations
	1	120/240 electric panel
	2	120V Electric 48" baseboard heater (+4" A.F.F.)
T	1	Thermostat (+54" A.F.F.)
⊖	5	120V ivory duplex grounding type (+18" AFF unless noted)
⊖	1	120V ivory single A/C Recept (+64" AFF)
◀	2	2x4- box w/3/4" conduit thru floor for phone/data (+28" AFF unless noted)
⊸	2	120V ivory toggle type (+48" AFF unless noted)
	1	120V 4' (2) tube surface mount w/diffuser
◇	1	120V Porcelain base incandescent light

Module: A — Area served: 308 ft — Panel Voltage: 240
Main Breaker: 60A — Panel Phase: 1

CKT#	Breaker size	Description	QTY	Voltage	Wattage per item	Connected Load	Load Factor	Calculated load	Total
1	20/1	A/C	1	120	840	840	1.00	840	840
2	20/1	Baseboard Heater	4	120	1000	4000	1.00	4000	4000
3	15/1	Lights	1	120	84	84	1.25	105	
		Exit Light	1	120	20	20	1.25	25	130
4	15/1	Recepts	1	120	180	180	1.00	180	180
							Total connected load		4370 VA
							Actual light load		109 VA
							125% of A/C		840 VA
							Total Calculated load	5.5	5019 VA
							Total Load		4929 VA
							Panel load amps		20.5 A

DOOR & WINDOW SCHEDULE

SYMBOL	QTY.	DESCRIPTION	ROUGH OPENING
A	2	36x80 standard vinyl clad door w/alum. frame and 10x10 safety glazed lite stay chain, knob lock set, weatherstripping and threashold	36 x 80 see R.O. Detail
B	1	72 X 68 Steel roll-up overhead	72 x 68 1/2
C	1	24x80 hollow core door w/factory frame and passage knob set	24 5/8 x 81 5/8
1	3	horizontal slider w/aluminum mill frame single glass, blinds and bug screen 4CX27	30 1/4" x 27 1/4" up 41 1/4" A.F.F.
2	2	36x14 horizontal slider w/aluminum mill frame single obscure glass and bug screen	30 1/4" x 14 1/4" up 54 1/4" A.F.F.

Wire Size Chart

Breaker Size	Wire Size	Breaker Size	Wire Size
15A	#14	90A	#3
20A	#12	100A	#3
30A	#10	110A	#2
40A	#8	115A	#1
50A	#6	125A	#1
60A	#6	150A	1/0