

DRAWING LEGEND

SYMBOL	QTY.	DESCRIPTION
	1	125A, 120/240V ELECTRICAL PANEL
	2	2' FLOOR DRAIN
	1	MAIN WATER SUPPLY INLET
	1	120 GAL., 240V ELECTRIC WATER HEATER W/ PAN


FLOOR PLAN

NOTE:

BLOCKING MUST BE INSTALLED FROM THE FOUNDATION TO THE STEEL FRAME DIRECTLY UNDER THE WATER HEATER.

DOOR & WINDOW SCHEDULE

SYMBOL	QTY.	DESCRIPTION	ROUGH OPENING
(A)	2	3680 VINYL DOOR W/ 10' WINDOW, STAY CHAIN, KEYED KNOB LOCKSET & DEADBOLT	38x80 3/4 FUR TO 36x80 PER DETAIL
(B)	2	3280 HOLLOW CORE W/ WOOD JAMB & PASSAGE KNOB LATCHSET	34 X 81 3/4
(C)	1	3280 HOLLOW CORE W/ WOOD JAMB & KEYED KNOB LOCKSET	34 X 81 3/4
(I)	5	3014 HORIZONTAL SLIDER W/ ALUM. FRAME, SINGLE PANE OBSCURE GLASS & SCREEN @ 66" A.F.F.	30 1/4 X 14 1/4



1. SCREW A 1"x4" TO THE BOTTOM OF THE DOOR HEADER FOR EASY REMOVAL.

2. SCREW A 2"x4" OVER A 3/8"x3/4" STRIP OF OSB TO THE JACK STUD FOR EASY REMOVAL.

EXTERIOR DOOR FRAMING